

UPH-160L 90°

UPH-160L 45°

UPH-125L 90°

UPH-125L 45°

UPH-125L 15°

UPH-105L 90°

UPH-105L 15°

Extended Handle 130cm (52")

Extended Handle 80cm (31")

EASY FIT Patent

Male EASYFIT

easy adjustment handle

Registered Community Design

NEW

Quality Technology Innovation

Torches with standard spare parts. See the UPH torches catalog

UPH-105L No high frequency start 105A

05831LA	Hand torch Heavy-Duty UPH-105L 15° 130cm (52")	EASYFIT connection
05831LB	Hand torch Heavy-Duty UPH-105L 15° 80cm (31")	EASYFIT connection
05831LC	Hand torch Heavy-Duty UPH-105L 90° 130cm (52")	EASYFIT connection
05831LD	Hand torch Heavy-Duty UPH-105L 90° 80cm (31")	EASYFIT connection

UPH-125L No high frequency start 125A

05931LA	Hand torch Heavy-Duty UPH-125L 15° 130cm (52")	EASYFIT connection
05931LB	Hand torch Heavy-Duty UPH-125L 15° 80cm (31")	EASYFIT connection
05931LE	Hand torch Heavy-Duty UPH-125L 45° 130cm (52")	EASYFIT connection
05931LF	Hand torch Heavy-Duty UPH-125L 45° 80cm (31")	EASYFIT connection
05931LC	Hand torch Heavy-Duty UPH-125L 90° 130cm (52")	EASYFIT connection
05931LD	Hand torch Heavy-Duty UPH-125L 90° 80cm (31")	EASYFIT connection

UPH-160L No high frequency start 160A

03931LC	Hand torch Heavy-Duty UPH-160L 45° 130cm (52")	EASYFIT connection
03931LD	Hand torch Heavy-Duty UPH-160L 45° 80cm (31")	EASYFIT connection
03931LA	Hand torch Heavy-Duty UPH-160L 90° 130cm (52")	EASYFIT connection
03931LB	Hand torch Heavy-Duty UPH-160L 90° 80cm (31")	EASYFIT connection

Extensions and Leads, Coaxial Cable

05286FX-L	Extension 7.5m,	Female EASYFIT 6pins -	Male EASYFIT 6pins
05288FX-L	Extension 15m,	Female EASYFIT 6pins -	Male EASYFIT 6pins
09782FX-L **	Lead assembly 7.5m,	Female EASYFIT 6pins -	Male EURO CONNECTOR 5pins
09787FX-L **	Lead assembly 15m,	Female EASYFIT 6pins -	Male EURO CONNECTOR 5pins
05286FX-HY1	Lead assembly 7.5m,	Female EASYFIT 6pins -	Male HY H-105 connection
05288FX-HY1	Lead assembly 15m,	Female EASYFIT 6pins -	Male HY H-105 connection
05286FX-HY2	Lead assembly 7.5m,	Female EASYFIT 6pins -	Male HY H-125 connection
05288FX-HY2	Lead assembly 15m,	Female EASYFIT 6pins -	Male HY H-125 connection
05286FX-TD	Lead assembly 7.5m,	Female EASYFIT 6pins -	Male TD connection
05288FX-TD	Lead assembly 15m,	Female EASYFIT 6pins -	Male TD connection

** Connection to the system to be confirmed on the purchase order